

JUNE 28 - 30, 2005 NORFOLK CONVENTION CENTER

## Open Architecture & SNSC2

**LCDR Joel MacRitchie** 

Open Architecture Branch
PEO Integrate Warfare Systems
29 June 2005





### Purpose




- Clarify Cost of COTS / Tech Refresh and OA Implementation / Refresh
- Illustrate Surface Navy Standard C2 / OA Strategy
- Explain Role of Common Component-Based Library Within OA Strategy



# Simple C2 System Logical / Physical View








## SNSC2 DD(X) Architectural Basis





Leverage DD(X) investment for Forward Fit & Backfit



### COTS Refresh vs. OACE Refresh



- Navy Transition to COTS Based on Congressional Mandates in 1994 and 1995 \*
- COTS Refresh is a Fact of Life Today that was not Well Understood When Mandated
- OA Implementation Path Provides Cost, Schedule, and Upgradeability Advantages Over COTS / Tech Refresh

<sup>\* &</sup>quot;...Secretary of Defense William Perry directed in June 1994 that DoD acquisitions should <a href="make">make</a> maximum use of performance specifications and commercial standards, thus increasing the opportunities to make use of commercial products. This was followed by the Federal Acquisition Streamlining Acts of 1994 and 1995 from Congress, which directed the increased use of commercial items..."



# What are the OA End States? OA Category Criteria



- Standards-Based Computing Environment
  - OA Category 3
  - Hardware / Software Independence
- Application Software Component Reuse
  - OA Category 4
  - Modular Code with Consistent Interfaces
  - Common Application Services (TSCE-I)
- Working to Align These Standards w/ Fn Guidance



### **Evolutionary States of Surface** Domain OA



Category 4 Open Category 4 Common Category 4 Enterprise Category 3 "Closed" "Layered" "Layered & Open" "Enterprise / Joint" "Common" Monolithic Weapon Acoustic Comms Control Control Monolithic **Applications Applications** Infrastructure Services Infrastructure Services Infrastructure Services **Hardware Middleware Middleware** Middleware **Middleware** and **Operating Operating System Operating System Operating System Operating System Environment Hardware** Hardware **Hardware** Hardware **Modular Applications Cross-Program Apps Cross-Domain Apps** "Unglue the Stack" Opens Up Vendor Base **Mixed Developer Base Mixed Developer Base** H/W & Software Isolation Prime Owns Arch Gov't Owns Arch Gov't Owns Arch **OA RETURNS** Ease of Warfighting Reduce Development **COTS Refresh Cost Reduce Development Upgrades Avoidance** & Maintenance Costs **Enables Interoperability Enables Competition Program Manager Control PM Interdependencies UNCLASSIFIED** 



# SNSC2 Layered Architectural Approach




#### Infrastructure:

- Common Services and APIs
- Flexibility to Support Forward-Fit and Back-Fit

#### **OACE CAT-3:**

- Standards-based Interfaces
- Commercial Mainstream Products and Technologies



#### Applications:

- Common Reusable Components
- Platform Specific Components

Total Ship Computing Environment (TSCE-I)

#### Focus:

- OA CAT-3 Compliant Environments on Aegis, DD(X) and SSDS
- Adopt DD(X) TSCE-I Across Programs as Standard Infrastructure
- Maximize Application Reuse Across Programs



# OA / FORCEnet Alignment OA Category Criteria




- OA Category 3
  - Native Pub/Sub Combat System Networking
  - Fn Apps Can "Subscribe" to CS Network Data
- OA Category 4
  - Built on Component Architecture
  - Fn Becomes a Reusable CS Component



# Simple C2 System Logical / Physical View









# Surface Navy Standard C2 Initiative Key Themes





- <u>Maximize Reuse</u> of Aegis OA and SSDS Combat System Products
  - DD(X) is the Foundational Architecture
- Established a <u>Common Capability</u> <u>Introduction</u> Approach for In-service ships Aligned to DD(X) Releases
  - Completed Delivery of First Common Components (TSCE-I)
    - Rel 2 TSCEI in place for DD(X), Aegis OA and SSDS OA
    - Rel 3 TSCEI on plan for June SNSC2I delivery
- <u>Introduce Candidate</u>
   <u>Technologies/Applications</u> through
   Open Business Model




Industry Working Together To Maximize SNSC2 Re-Use



# Planned Reuse of DD(X) into Aegis and SSDS








### Surface Navy Standard C2

**Component Development Guidelines** 






- Industry-Defined Set of Guidelines to be used by all Component Developers
  - Specific subset of current OACE guidance and standards documents
  - Standards, attributes and conventions used
- Guidelines/Conventions Ensure:
  - Maximum Flexibility Latitude within the development community – (i.e., not overlyconstrained)
  - Minimize Constraints / Barriers to entry to allow wide participation
  - Efficient communications among potential disparate communities



### Surface Navy Standard C2

**Component Control Points** 








### Surface Navy OA Strategic Vision







### Summary



- Leveraging COTS Refresh to Implement OA
- Surface Navy Standard C2 / OA Strategy Dovetails with FORCEnet Precepts
- Common Component Library Necessary for Realization of Both OA Cat 4 and FORCEnet